

UT383/UT383BT can effectively measure light intensity and display results in units of Lux or Fc. UT383BT can transfer measurement data through Bluetooth to UNI-T's custom mobile APP (iENV2.0) for further analysis, storage, and export. iENV2.0 can be downloaded from Google Play, Apple Store, or UNI-T's website by searching 'iENV2.0'.



(UT383BT)



(UT383BT)



UT383BT

| Specifications | UT383 | UT383BT |
|-------------------------------|--------------------------------|--------------|
| Certificates | CE, UKCA | |
| Illuminance measurement (Lux) | 0~199,900Lux | 0~199,900Lux |
| Illuminance measurement (Fc) | 0~18,500Fc | 0~18,500Fc |
| Accuracy | ±(4%+8) | |
| Resolution | 1Lux (0~9999Lux) | |
| | 10Lux (≥10,000Lux) | |
| | 100Lux (≥100,000Lux) | |
| | 1Fc (0~9999Fc); FC=Lux/10.76 | |
| Sampling time | 10Fc (≥10,000Fc); FC=Lux/10.76 | |
| Bluetooth APP | | √ |
| Tripod mounting hole | | √ |

| Features | |
|---------------------|------------------------|
| MAX/MIN | Data hold |
| LCD backlight | Auto power off |
| Overload indication | Low battery indication |

| Characteristics | |
|------------------------------|--|
| Standard accessories | Batteries, English manual |
| Power | 1.5V battery (R03) x 3 |
| Display | 32 x 26mm |
| Product size | 160 x 50 x 28mm |
| Product net weight | 118g |
| Standard individual packing | Blister |
| Standard quantity per carton | UT383: 40pcs; UT383BT: 20pcs |
| Standard carton measurement | UT383: 505 x 330 x 280mm; UT383BT: 332 x 262 x 290mm |
| Standard carton gross weight | UT383: 8.42kg; UT383BT: 4.2kg |